



Flowmeters and Switches

Flow Indicator with Rotor
Brass, stainless steel
Model: DAA, DAH



Water: 0.1 – 3 GPM to 1 – 58 GPM
 t_{max} 210 °F; p_{max} 230 PSIG
Connection: 1/4" to 1 1/2" NPT

Flow Indicator with Rotor
Brass, stainless steel
Model: DAF



Water:
0.16 – 0.16 GPH to 100 – 2,400 GPH
 t_{max} 180 °F; p_{max} 230 PSIG
Connection: 1/8" to 1 1/2" NPT, 1/2" to 2" ANSI

Flow Indicator with Rotor
Grey cast iron, cast steel, stainless steel
Model: DAR-1



t_{max} 500 °F; p_{max} 580 PSIG
Connection: 1/4" to 2" NPT

Flow Indicator with Rotor
Grey cast iron, cast steel, stainless steel
Model: DAR-2



t_{max} 500 °F; p_{max} 580 PSIG
Connection: 1/2" to 8" ANSI

Flow Indicator with Rotor
Brass
Model: DKF



Water: 0.03 – 1.8 GPM to 0.08 – 16 GPM
 t_{max} 250 °F; p_{max} 85 PSIG
Connection: 1/8" to 1" NPT

Flow Indicator with Rotor
Brass, stainless steel, Delrin, PVDF
Model: DIH



Water: 0.05 – 0.2 GPM to 0.66 – 13.2 GPM
 t_{max} 175 °F; p_{max} 230 PSIG
Connection: 3/8" NPT or 1" NPT

Flow Indicator with Rotor
PP, bronze, stainless steel
Model: DIG



Water: 0.15 – 3 GPM to 3 – 37 GPM
 t_{max} 175 °F; p_{max} 230 PSIG
Connection: 1/8" to 1" NPT

Flow Indicator with Flap
Grey cast iron, cast steel, stainless steel
Model: DAK-1



t_{max} 530 °F; p_{max} 580 PSIG
Connection: 1/4" to 2" NPT

Flow Indicator with Flap
Grey cast iron, cast steel, stainless steel
Model: DAK-2



t_{max} 530 °F; p_{max} 580 PSIG
Connection: 1/2" to 8" ANSI

Flow Indicator with Ball
Brass
Model: DKB



Water: 0.03 – 1.8 GPM to 0.08 – 16 GPM
 t_{max} 250 °F; p_{max} 85 PSIG
Connection: 1/8" to 1" NPT

Flow Indicator with Drip Tube
Grey cast iron, cast steel, stainless steel
Model: DAT



t_{max} 250 °F; p_{max} 85 PSIG
Connection: 1/4" to 2" NPT, 1/2" to 8" ANSI

Flow Indicator - Sight Glass
Stainless Steel, PVC
Model: UFJ



t_{max} 210 °F; p_{max} 145 PSIG
Connection: 1/4" to 2" BSP